



**Summary of Substantive Changes
between the 2012 and the 2014 editions of
ASTM D2665 “Poly(Vinyl Chloride) (PVC) Plastic Drain, Waste, and Vent
Pipe and Fittings”**

Presented to the IAPMO Standards Review Committee on September 8, 2014

General: The changes to this standard should not have an impact on currently listed products. The substantive changes are:

- Added an exemption from the impact resistance requirements for bushings increasers and closet flanges (see Section 6.4)
- Reduced the impact resistance requirement for NPS-2 and smaller fittings from 15 ft·lb (20 J) to 7.5 ft·lb (10 J) (see Table 4)

Section 6.4 Impact Resistance: Added an exemption from the impact resistance requirements for bushings increasers and closet flanges as follows:

[6.4.3 Bushings increasers and closet flanges are exempt from this requirement.](#)

Table 4, Impact Resistance of PVC Plastic Drain, Waste and Vent Pipe and Fittings: Reduced the impact resistance requirement for NPS-2 and smaller fittings from 15 ft·lb (20 J) to 7.5 ft·lb (10 J) as follows:

**TABLE 4 Impact Resistance of PVC Plastic Drain, Waste and Vent
Pipe and Fittings**

<i>Description</i>	<i>Impact Resistance, min., ft-lbf (J) 73°F (23°C)</i>
<i>All pipe sizes</i>	<i>60 (81)</i>
All fitting sizes and types <u>(larger than 2 in. nominal OD)</u>	<i>15 (20)</i>
<u>Fitting sizes and types (2 in. and smaller nominal OD)</u>	<u>7.5 (10)</u>